NSN 5935-01-310-2828

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-310-2828

Body Style:
Right angle type
Overall Length:
3.850 inches
Overall Height:
0.520 inches
Overall Width:
0.545 inches
Unthreaded Mounting Hole Diameter:
0.098 inches
Distance Between Mounting Facility Centers:
3.600 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
1.5 single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Friction
Terminal Location:
Side single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Contact Surface Treatment Specification:
Mil-g-45204, type ii, class 2, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290,
class 2 federal specification 2nd treatment response single mating end single contact grouping
Terminal Type:
Pin single mating end single contact grouping
Contact Material Specification:
Qq-c-626 federal specification single material response single mating end single contact grouping or qq-c-530 federal specification single
material response single mating end single contact grouping or qq-b-750 federal specification single material response single mating end
single contact grouping

Shell Material Specification:

Shell Material:

Plastic

Mil-m-24519, type gst-40f military specification single material response

Included Contact Quantity:

128 single mating and single contact grouping

NSN 5935-01-310-2828

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Round pin single mating end single contact grouping
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.