NSN 5935-01-310-3095

Tip Jack - Page 1 of 2

Electrical Insulation Feature:

Uninsulated **Body Style:**



View Online at https://aerobasegroup.com/nsn/5935-01-310-3095

Press fit mounted
Mounting Bushing Length:
0.125 inches
Body Length:
0.317 inches
Overall Diameter:
0.125 inches
Bushing Accommodation Hole Shape:
Round
Accommodated Finger Type:
Test prod single finger
Finger Accommodation Diameter:
0.040 inches single finger
Finger Accommodation Length:
0.192 inches single finger
Mounting Bushing Diameter:
Between 0.083 inches and 0.087 inches
Bushing Thru-hole Accommodation Diameter:
Between 0.087 inches and 0.091 inches
End Application:
5820-01-145-8503 monitor, radio frequency
Mounting Facility Type And Quantity:
1 bushing
Terminal Type:
Printed circuit
Material:
Material: Brass body
Brass body
Brass body Material:
Brass body Material: Copper alloy spring
Brass body Material: Copper alloy spring Precious Material And Location:
Brass body Material: Copper alloy spring Precious Material And Location: Contact surface gold
Brass body Material: Copper alloy spring Precious Material And Location: Contact surface gold Precious Material:
Brass body Material: Copper alloy spring Precious Material And Location: Contact surface gold Precious Material: Gold
Brass body Material: Copper alloy spring Precious Material And Location: Contact surface gold Precious Material: Gold Surface Treatment:
Brass body Material: Copper alloy spring Precious Material And Location: Contact surface gold Precious Material: Gold Surface Treatment: Gold and copper spring
Brass body Material: Copper alloy spring Precious Material And Location: Contact surface gold Precious Material: Gold Surface Treatment: Gold and copper spring Surface Treatment:
Brass body Material: Copper alloy spring Precious Material And Location: Contact surface gold Precious Material: Gold Surface Treatment: Gold and copper spring Surface Treatment: Gold spring and copper spring

NSN 5935-01-310-3095

Tip Jack - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A03400