

View Online at <https://aerobasegroup.com/nsn/5935-01-311-2997>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

Between 33.5 millimeters and 34.1 millimeters

Overall Height:

Between 37.7 millimeters and 38.3 millimeters

Overall Width:

Between 37.7 millimeters and 38.3 millimeters

Environmental Protection:

Fuel resistant and shock resistant and vibration resistant and waterproof

Unthreaded Mounting Hole Diameter:

Between 3.2 millimeters and 3.3 millimeters

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 29.3 millimeters and 29.5 millimeters

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 29.3 millimeters and 29.5 millimeters

Distance From Mounting Shoulder To Front Face:

Between 19.0 millimeters and 19.4 millimeters

Threaded Device Type:

Back shell

Mating End Quantity:

1

Contact Position Arrangement Style:

20-27 single mating end

Contact Removability:

Removable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

22.0 single mating end all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end 1st contact grouping

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end 1st contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet latch

End Application:

2350-0-281-6450 carrier, carg0

Operating Temperature Rating:

Between -55.0 degrees celsius and 125.0 degrees celsius

Thready Qty Per Inch (tpi):

18

Thread Size:

1.125 inches

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings or silver single mating end all contact groupings or rhodium single mating end all contact groupings

Insert Material:

Rubber single mating end

Terminal Type:

Crimp single mating end all contact groupings

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and chromate

Shell Surface Treatment Specification:

Qq-p-416, cl 2, type 2 federal specification all treatment responses

Included Contact Quantity:

8 single mating end 2nd contact grouping

Included Contact Type:

Round socket single mating end all contact groupings

Precious Material And Location:

Contact surfaces gold or contact surfaces silver or contact surfaces rhodium

Precious Material And Weight:

0.014 gold grains, troy or 0.014 silver grains, troy or 0.014 rhodium grains, troy

Precious Material:

Gold or silver or rhodium

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0