NSN 5935-01-311-3675

Electrical Receptacle Connector Body - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-311-3675 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 2.000 inches **Overall Height:** 2.260 inches **Overall Width:** 2.260 inches **Environmental Protection:** Moisture proof and salt water resistant and vibration proof and shock resistant and cold resistant and heat resistant and explosion proof **Unthreaded Mounting Hole Diameter:** 0.175 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** 1.750 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.750 inches **Distance From Mounting Shoulder To Front Face:** 0.890 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 32-2010-60 single mating end **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 250.0 Shell Type: Solid **Connector Locking Method:** Externally threaded shell **Operating Tempurature Rating:** Between -55.0 degrees celsius and 125.0 degrees celsius Thready Qty Per Inch (tpi): 18

10

Thread Size:

2.000 inches

NSN 5935-01-311-3675

Electrical Receptacle Connector Body - Page 2 of 2



Insert Material:
Rubber single mating end
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification all treatment responses
Thread Series Designator:
Uns
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia:

A039b0