NSN 5935-01-311-4426

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-311-4426

Body Style:

Straight shape, internal coupling

Overall Length:

1.980 inches

Overall Diameter:

Between 0.740 inches and 0.760 inches

Cable Entrance Diameter:

Between 0.240 inches and 0.245 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

Nonstd single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Bayonet slot

Connector Cable Strain Relief Method:

Compression nut

End Application:

An/wsn-7 (v) 1, subsurface ring laser gyro inertial nav sys; an/wsn-7 (v) 2, surface ring laser gyro inertial nav sys; an/wsn-7 (v)1, surface ring laser gyro inertial nav sys; computer, an/uyk-4 (v); los angeles class ssn (688); an/wsn-7 (v)2, subsurface ring laser gyro inertial nav sys; spruance class dd (963); virginia class cgn (41); an/wsn-7 (v) surface 3 ring laser gyro inertial nav sys; ticonderoga class cg (47)

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper alloy single mating end single contact grouping

Criticality Code Justification:

Feat

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Metal

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial pin single mating end single contact grouping

Special Features:

Weapon system essential

NSN 5935-01-311-4426

A039b0

Electrical Plug Connector - Page 2 of 2



Precious Material:
Gold
Test Data Document:
94756-414-2945 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: