

View Online at <https://aerobasegroup.com/nsn/5935-01-311-4675>

Body Style:

Straight shape, external coupling

Overall Length:

2.031 inches

Overall Diameter:

1.772 inches

Distance From Mounting Shoulder To Front Face:

0.720 inches

Mounting Facility Thickness:

0.126 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

16s-1 single mating end

Contact Maximum Current Rating In Amps:

22.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

80.0

Shell Type:

Solid

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Included Contact Quantity:

7 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Test Data Document:

81349-mil-c-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-c-5015 spec.