## NSN 5935-01-311-4676

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-311-4676 **Body Style:** Straight shape, external coupling **Overall Length:** 2.125 inches Overall Diameter: 1.897 inches **Distance From Mounting Shoulder To Front Face:** 0.970 inches **Mounting Facility Thickness:** 0.126 inches **Mating End Quantity: Contact Position Arrangement Style:** 18-1 single mating end **Contact Maximum Current Rating In Amps:** 22.0 single mating end all contact groupings **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end 1st contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end 1st contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 70.0 **Terminal Type:** Crimp single mating end all contact groupings **Shell Material:** Aluminum alloy **Included Contact Quantity:** 6 single mating end 2nd contact grouping **Included Contact Type:** Round socket single mating end all contact groupings **Test Data Document:** 81349-mil-c-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

Fiig: A039b0

No

## NSN 5935-01-311-4676

Electrical Receptacle Connector - Page 2 of 2



Mil-std (military Standard):

Mil-c-5015 spec.