

View Online at <https://aerobasegroup.com/nsn/5935-01-311-5346>

Thread Class:

2a

Thread Direction:

Right-hand and right-hand and right-hand

Body Style:

Straight shape, external coupling

Overall Length:

32.5 millimeters

Overall Diameter:

Between 41.0 millimeters and 41.6 millimeters

Environmental Protection:

Moisture proof and salt water resistant and vibration proof and corrosion resistant and dust resistant and fuel resistant and fungus resistant and humidity resistant and oil resistant and shock resistant and thermal shock resistant and vibration resistant

Distance From Mounting Shoulder To Front Face:

22.6 millimeters

Mounting Facility Thickness:

Between 1.58 millimeters and 3.20 millimeters

Threaded Device Type:

Back shell and coupling facility and mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

15-35 single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0 and 108.0 and 165.0 and 215.0 and 270.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thread Length:

7.11 millimeters

Operating Temperature Rating:

Between -65.0 degrees celsius and 175.0 degrees celsius

Features Provided:

Color band engagement indicator

Thread Qty Per Inch (tpi):

10

Thread Size:

22.0 millimeters and 1.000 inches and 28.0 millimeters

Thread Pitch In Millimeters:

1.00 and 1.00

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic epoxy single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

Thread Tolerance Class:

6g external and 6g external

Included Contact Quantity:

37 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round w/flat

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.037 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-dod-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Iso m and special acme and iso m

Specification Data:

81349-dod-c-38999/24 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.