NSN 5935-01-311-6313

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-311-6313

Body Style:

Right angle, type

Overall Length:

Between 4.496 inches and 4.536 inches

Overall Height:

0.694 inches

Overall Width:

0.461 inches

Unthreaded Mounting Hole Diameter:

0.157 inches

Distance Between Mounting Facility Centers:

4.200 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Connector Locking Method:

Friction

Operating Tempurature Rating:

Between -55.0 degrees celsius and 125.0 degrees celsius

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Pin single mating end single contact grouping

Guide Design And Location:

Key shape pin left-hand at 3 oclock and key shape socket right-hand at 3 oclock

Included Contact Quantity:

72 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

NSN 5935-01-311-6313

Electrical Receptacle Connector - Page 2 of 2



Special Features:
Pin protectors on item
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.072 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0