1

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-311-6313

## **Body Style:** Right angle, type **Overall Length:** Between 4.496 inches and 4.536 inches **Overall Height:** 0.694 inches **Overall Width:** 0.461 inches **Unthreaded Mounting Hole Diameter:** 0.157 inches **Distance Between Mounting Facility Centers:** 4.200 inches Mating End Quantity: **Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Guide pin/socket **Connector Locking Method:** Friction **Operating Tempurature Rating:** Between -55.0 degrees celsius and 125.0 degrees celsius **Terminal Location:** Side single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Pin single mating end single contact grouping **Guide Design And Location:** Key shape pin left-hand at 3 oclock and key shape socket right-hand at 3 oclock **Included Contact Quantity:** 72 single mating end single contact grouping **Included Contact Type:**

Round pin single mating end single contact grouping



**Special Features:** 

Pin protectors on item

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.072 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0