Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-311-6322

Body Style:
Straight shape
Overall Length:
1.624 inches
Overall Height:
Between 3.742 inches and 3.762 inches
Overall Width:
Between 3.380 inches and 3.400 inches
Unthreaded Mounting Hole Diameter:
Between 0.156 inches and 0.176 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 0.995 inches and 1.015 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 2.870 inches and 2.890 inches
Distance From Mounting Shoulder To Front Face:
Between 0.067 inches and 0.087 inches
Mating End Quantity:
2
Contact Position Arrangement Style:
10 all mating ends
Contact Removability:
Nonremovable all mating ends all contact groupings
Contact Maximum Current Rating In Amps:
20.0 1st mating end 2nd contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Connector Locking Method:
Friction
Terminal Location:
Back all mating ends all contact groupings
Contact Material:
Copper alloy all mating ends all contact groupings
Contact Surface Treatment:
Gold all mating ends all contact groupings
Insert Material:
Plastic diallyl phthalate all mating ends
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response all mating ends all contact groupings
Criticality Code Justification:
Zzzy

Electrical Receptacle Connector - Page 2 of 2



# Terminal Type:

Solder well all mating ends all contact groupings

## **Contact Material Specification:**

Qq-c-533 federal specification single material response all mating ends all contact groupings

### Shell Material:

Aluminum alloy 380.0

# Shell Surface Treatment:

Cadmium

## Shell Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

## **Shell Material Specification:**

Qq-a-501 federal specification single material response

## **Insert Material Specification:**

Mil-m-14 military specification single material response all mating ends

### **Included Contact Quantity:**

6 1st mating end 2nd contact grouping

### Included Contact Type:

Round pin all mating ends all contact groupings

#### **Special Features:**

Item must comply with requirements of defense supply center columbus production standard no. Lo4131

**Precious Material And Location:** 

Contact surfaces gold

#### **Precious Material And Weight:**

0.052 gold grains, troy

Precious Material:

Gold

## **Reference Number Differentiating Characteristics:**

Areference number differentiating material will be in accordance with naval inventory control point activity hx quality control. Manufacturing

and testing specifications available at the dla  $\operatorname{icp}$ 

## Shelf Life:

N/a

## Unit Of Measure:

```
--
```

# Demilitarization:

No

## Fiig:

A039b0

## Mil-std (military Standard):

Mil-g-45204 spec.