## NSN 5935-01-312-0564

Thread Class: 2a and 2b

Right-hand **Body Style:** 

**Thread Direction:** 

Overall Length: 1.750 inches

Straight shape w/screw locks

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-312-0564

Overall Width:  0.375 inches Threaded Device Type: Coupling facility Mating End Quantity:  1 Contact Position Arrangement Style: 9 single mating end Contact Removability: Nonremovable single mating end all contact groupings Contact Maximum Current Rating In Amps: 23.0 single mating end 1st contact grouping Polarization Method: Contact and jackscrew Connector Locking Method: Jackscrew-socket Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Terminal Location: Back single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings Contact Surface Treatment: Gold single mating end all contact groupings Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end all contact groupings	
Threaded Device Type: Coupling facility Mating End Quantity:  1 Contact Position Arrangement Style: 9 single mating end Contact Removability: Nonremovable single mating end all contact groupings Contact Maximum Current Rating In Amps: 23.0 single mating end 1st contact grouping Polarization Method: Contact and jackscrew Connector Locking Method: Jackscrew-socket Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Terminal Location: Back single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings Contact Surface Treatment: Gold single mating end all contact groupings Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end all contact groupings	
Threaded Device Type: Coupling facility Mating End Quantity:  1 Contact Position Arrangement Style: 9 single mating end Contact Removability: Nonremovable single mating end all contact groupings Contact Maximum Current Rating In Amps: 23.0 single mating end 1st contact grouping Polarization Method: Contact and jackscrew Connector Locking Method: Jackscrew-socket Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Terminal Location: Back single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings Contact Surface Treatment: Gold single mating end all contact groupings Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end all contact groupings	
Coupling facility  Mating End Quantity:  1  Contact Position Arrangement Style: 9 single mating end Contact Removability: Nonremovable single mating end all contact groupings Contact Maximum Current Rating In Amps: 23.0 single mating end 1st contact grouping Polarization Method: Contact and jackscrew Connector Locking Method: Jackscrew-socket Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Terminal Location: Back single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings Contact Surface Treatment: Gold single mating end all contact groupings Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end all contact groupings	
Mating End Quantity:  1 Contact Position Arrangement Style: 9 single mating end Contact Removability: Nonremovable single mating end all contact groupings Contact Maximum Current Rating In Amps: 23.0 single mating end 1st contact grouping Polarization Method: Contact and jackscrew Connector Locking Method: Jackscrew-socket Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Terminal Location: Back single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings Contact Surface Treatment: Gold single mating end all contact groupings Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end all contact groupings	
Contact Position Arrangement Style:  9 single mating end Contact Removability: Nonremovable single mating end all contact groupings Contact Maximum Current Rating In Amps: 23.0 single mating end 1st contact grouping Polarization Method: Contact and jackscrew Connector Locking Method: Jackscrew-socket Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Terminal Location: Back single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings Contact Surface Treatment: Gold single mating end all contact groupings Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end all contact groupings	
Contact Position Arrangement Style:  9 single mating end Contact Removability: Nonremovable single mating end all contact groupings Contact Maximum Current Rating In Amps: 23.0 single mating end 1st contact grouping Polarization Method: Contact and jackscrew Connector Locking Method: Jackscrew-socket Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Terminal Location: Back single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings Contact Surface Treatment: Gold single mating end all contact groupings Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end all contact groupings	
9 single mating end Contact Removability: Nonremovable single mating end all contact groupings Contact Maximum Current Rating In Amps: 23.0 single mating end 1st contact grouping Polarization Method: Contact and jackscrew Connector Locking Method: Jackscrew-socket Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Terminal Location: Back single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings Contact Surface Treatment: Gold single mating end all contact groupings Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end all contact groupings	
Contact Removability:  Nonremovable single mating end all contact groupings  Contact Maximum Current Rating In Amps:  23.0 single mating end 1st contact grouping  Polarization Method:  Contact and jackscrew  Connector Locking Method:  Jackscrew-socket  Thready Qty Per Inch (tpi):  32  Thread Size:  0.138 inches  Terminal Location:  Back single mating end all contact groupings  Contact Material:  Copper alloy single mating end all contact groupings  Contact Surface Treatment:  Gold single mating end all contact groupings  Insert Material:  Plastic diallyl phthalate single mating end  Terminal Type:  Solder well single mating end all contact groupings	
Nonremovable single mating end all contact groupings  Contact Maximum Current Rating In Amps:  23.0 single mating end 1st contact grouping  Polarization Method:  Contact and jackscrew  Connector Locking Method:  Jackscrew-socket  Thready Qty Per Inch (tpi):  32  Thread Size:  0.138 inches  Terminal Location:  Back single mating end all contact groupings  Contact Material:  Copper alloy single mating end all contact groupings  Contact Surface Treatment:  Gold single mating end all contact groupings  Insert Material:  Plastic diallyl phthalate single mating end  Terminal Type:  Solder well single mating end all contact groupings	
Contact Maximum Current Rating In Amps: 23.0 single mating end 1st contact grouping Polarization Method: Contact and jackscrew Connector Locking Method: Jackscrew-socket Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Terminal Location: Back single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings Contact Surface Treatment: Gold single mating end all contact groupings Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end all contact groupings	
Polarization Method: Contact and jackscrew Connector Locking Method: Jackscrew-socket Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Terminal Location: Back single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings Contact Surface Treatment: Gold single mating end all contact groupings Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end all contact groupings	
Polarization Method: Contact and jackscrew Connector Locking Method: Jackscrew-socket Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Terminal Location: Back single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings Contact Surface Treatment: Gold single mating end all contact groupings Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end all contact groupings	
Connector Locking Method:  Jackscrew-socket Thready Qty Per Inch (tpi):  32 Thread Size: 0.138 inches Terminal Location: Back single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings Contact Surface Treatment: Gold single mating end all contact groupings Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end all contact groupings	
Connector Locking Method: Jackscrew-socket Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Terminal Location: Back single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings Contact Surface Treatment: Gold single mating end all contact groupings Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end all contact groupings	
Thready Qty Per Inch (tpi):  32 Thread Size: 0.138 inches Terminal Location: Back single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings Contact Surface Treatment: Gold single mating end all contact groupings Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end all contact groupings	
Thready Qty Per Inch (tpi):  32 Thread Size: 0.138 inches Terminal Location: Back single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings Contact Surface Treatment: Gold single mating end all contact groupings Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end all contact groupings	
Thread Size: 0.138 inches Terminal Location: Back single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings Contact Surface Treatment: Gold single mating end all contact groupings Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end all contact groupings	
Thread Size:  0.138 inches  Terminal Location:  Back single mating end all contact groupings  Contact Material:  Copper alloy single mating end all contact groupings  Contact Surface Treatment:  Gold single mating end all contact groupings  Insert Material:  Plastic diallyl phthalate single mating end  Terminal Type:  Solder well single mating end all contact groupings	
O.138 inches  Terminal Location:  Back single mating end all contact groupings  Contact Material:  Copper alloy single mating end all contact groupings  Contact Surface Treatment:  Gold single mating end all contact groupings  Insert Material:  Plastic diallyl phthalate single mating end  Terminal Type:  Solder well single mating end all contact groupings	
Terminal Location:  Back single mating end all contact groupings  Contact Material:  Copper alloy single mating end all contact groupings  Contact Surface Treatment:  Gold single mating end all contact groupings  Insert Material:  Plastic diallyl phthalate single mating end  Terminal Type:  Solder well single mating end all contact groupings	
Back single mating end all contact groupings  Contact Material:  Copper alloy single mating end all contact groupings  Contact Surface Treatment:  Gold single mating end all contact groupings  Insert Material:  Plastic diallyl phthalate single mating end  Terminal Type:  Solder well single mating end all contact groupings	
Contact Material: Copper alloy single mating end all contact groupings Contact Surface Treatment: Gold single mating end all contact groupings Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end all contact groupings	
Copper alloy single mating end all contact groupings  Contact Surface Treatment:  Gold single mating end all contact groupings  Insert Material:  Plastic diallyl phthalate single mating end  Terminal Type:  Solder well single mating end all contact groupings	
Contact Surface Treatment:  Gold single mating end all contact groupings Insert Material:  Plastic diallyl phthalate single mating end Terminal Type:  Solder well single mating end all contact groupings	
Gold single mating end all contact groupings Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end all contact groupings	
Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end all contact groupings	
Plastic diallyl phthalate single mating end  Terminal Type:  Solder well single mating end all contact groupings	
Terminal Type: Solder well single mating end all contact groupings	
Solder well single mating end all contact groupings	
Insert Material Specification:	
Mil-m-14 military specification single material response single mating end	

## NSN 5935-01-312-0564

Electrical Plug Connector - Page 2 of 2



## **Included Contact Quantity:** 5 single mating end 2nd contact grouping **Included Contact Type:** Round socket single mating end all contact groupings **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.009 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** Demilitarization: No Fiig:

A039b0

Mil-m-14 spec.

Mil-std (military Standard):