NSN 5935-01-312-0564

Thread Class: 2a and 2b

Right-hand **Body Style:**

Thread Direction:

Overall Length: 1.750 inches

Straight shape w/screw locks

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-312-0564

Overall Width: 0.375 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 9 single mating end Contact Removability: Nonremovable single mating end all contact groupings Contact Maximum Current Rating In Amps: 23.0 single mating end 1st contact grouping Polarization Method: Contact and jackscrew Connector Locking Method: Jackscrew-socket Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Terminal Location: Back single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings Contact Surface Treatment: Gold single mating end all contact groupings Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end all contact groupings	
Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 9 single mating end Contact Removability: Nonremovable single mating end all contact groupings Contact Maximum Current Rating In Amps: 23.0 single mating end 1st contact grouping Polarization Method: Contact and jackscrew Connector Locking Method: Jackscrew-socket Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Terminal Location: Back single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings Contact Surface Treatment: Gold single mating end all contact groupings Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end all contact groupings	
Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 9 single mating end Contact Removability: Nonremovable single mating end all contact groupings Contact Maximum Current Rating In Amps: 23.0 single mating end 1st contact grouping Polarization Method: Contact and jackscrew Connector Locking Method: Jackscrew-socket Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Terminal Location: Back single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings Contact Surface Treatment: Gold single mating end all contact groupings Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end all contact groupings	
Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 9 single mating end Contact Removability: Nonremovable single mating end all contact groupings Contact Maximum Current Rating In Amps: 23.0 single mating end 1st contact grouping Polarization Method: Contact and jackscrew Connector Locking Method: Jackscrew-socket Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Terminal Location: Back single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings Contact Surface Treatment: Gold single mating end all contact groupings Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end all contact groupings	
Mating End Quantity: 1 Contact Position Arrangement Style: 9 single mating end Contact Removability: Nonremovable single mating end all contact groupings Contact Maximum Current Rating In Amps: 23.0 single mating end 1st contact grouping Polarization Method: Contact and jackscrew Connector Locking Method: Jackscrew-socket Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Terminal Location: Back single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings Contact Surface Treatment: Gold single mating end all contact groupings Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end all contact groupings	
Contact Position Arrangement Style: 9 single mating end Contact Removability: Nonremovable single mating end all contact groupings Contact Maximum Current Rating In Amps: 23.0 single mating end 1st contact grouping Polarization Method: Contact and jackscrew Connector Locking Method: Jackscrew-socket Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Terminal Location: Back single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings Contact Surface Treatment: Gold single mating end all contact groupings Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end all contact groupings	
Contact Position Arrangement Style: 9 single mating end Contact Removability: Nonremovable single mating end all contact groupings Contact Maximum Current Rating In Amps: 23.0 single mating end 1st contact grouping Polarization Method: Contact and jackscrew Connector Locking Method: Jackscrew-socket Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Terminal Location: Back single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings Contact Surface Treatment: Gold single mating end all contact groupings Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end all contact groupings	
9 single mating end Contact Removability: Nonremovable single mating end all contact groupings Contact Maximum Current Rating In Amps: 23.0 single mating end 1st contact grouping Polarization Method: Contact and jackscrew Connector Locking Method: Jackscrew-socket Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Terminal Location: Back single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings Contact Surface Treatment: Gold single mating end all contact groupings Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end all contact groupings	
Contact Removability: Nonremovable single mating end all contact groupings Contact Maximum Current Rating In Amps: 23.0 single mating end 1st contact grouping Polarization Method: Contact and jackscrew Connector Locking Method: Jackscrew-socket Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Terminal Location: Back single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings Contact Surface Treatment: Gold single mating end all contact groupings Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end all contact groupings	
Nonremovable single mating end all contact groupings Contact Maximum Current Rating In Amps: 23.0 single mating end 1st contact grouping Polarization Method: Contact and jackscrew Connector Locking Method: Jackscrew-socket Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Terminal Location: Back single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings Contact Surface Treatment: Gold single mating end all contact groupings Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end all contact groupings	
Contact Maximum Current Rating In Amps: 23.0 single mating end 1st contact grouping Polarization Method: Contact and jackscrew Connector Locking Method: Jackscrew-socket Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Terminal Location: Back single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings Contact Surface Treatment: Gold single mating end all contact groupings Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end all contact groupings	
Polarization Method: Contact and jackscrew Connector Locking Method: Jackscrew-socket Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Terminal Location: Back single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings Contact Surface Treatment: Gold single mating end all contact groupings Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end all contact groupings	
Polarization Method: Contact and jackscrew Connector Locking Method: Jackscrew-socket Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Terminal Location: Back single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings Contact Surface Treatment: Gold single mating end all contact groupings Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end all contact groupings	
Connector Locking Method: Jackscrew-socket Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Terminal Location: Back single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings Contact Surface Treatment: Gold single mating end all contact groupings Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end all contact groupings	
Connector Locking Method: Jackscrew-socket Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Terminal Location: Back single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings Contact Surface Treatment: Gold single mating end all contact groupings Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end all contact groupings	
Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Terminal Location: Back single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings Contact Surface Treatment: Gold single mating end all contact groupings Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end all contact groupings	
Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Terminal Location: Back single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings Contact Surface Treatment: Gold single mating end all contact groupings Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end all contact groupings	
Thread Size: 0.138 inches Terminal Location: Back single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings Contact Surface Treatment: Gold single mating end all contact groupings Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end all contact groupings	
Thread Size: 0.138 inches Terminal Location: Back single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings Contact Surface Treatment: Gold single mating end all contact groupings Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end all contact groupings	
O.138 inches Terminal Location: Back single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings Contact Surface Treatment: Gold single mating end all contact groupings Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end all contact groupings	
Terminal Location: Back single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings Contact Surface Treatment: Gold single mating end all contact groupings Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end all contact groupings	
Back single mating end all contact groupings Contact Material: Copper alloy single mating end all contact groupings Contact Surface Treatment: Gold single mating end all contact groupings Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end all contact groupings	
Contact Material: Copper alloy single mating end all contact groupings Contact Surface Treatment: Gold single mating end all contact groupings Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end all contact groupings	
Copper alloy single mating end all contact groupings Contact Surface Treatment: Gold single mating end all contact groupings Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end all contact groupings	
Contact Surface Treatment: Gold single mating end all contact groupings Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end all contact groupings	
Gold single mating end all contact groupings Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end all contact groupings	
Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end all contact groupings	
Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end all contact groupings	
Terminal Type: Solder well single mating end all contact groupings	
Solder well single mating end all contact groupings	
Insert Material Specification:	
Mil-m-14 military specification single material response single mating end	

NSN 5935-01-312-0564

Electrical Plug Connector - Page 2 of 2



Included Contact Quantity: 5 single mating end 2nd contact grouping **Included Contact Type:** Round socket single mating end all contact groupings **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.009 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** Demilitarization: No Fiig:

A039b0

Mil-m-14 spec.

Mil-std (military Standard):