## NSN 5935-01-312-1806

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-312-1806 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.016 inches **Overall Diameter:** 2.031 inches **Distance From Mounting Shoulder To Front Face:** 0.438 inches **Mounting Facility Thickness:** 0.109 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 18-35 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid Thready Qty Per Inch (tpi): 18 **Thread Size:** 1.500 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic epoxy single mating end

Terminal Type:

Crimp single mating end single contact grouping

## NSN 5935-01-312-1806

Electrical Receptacle Connector - Page 2 of 2



| Shell Material:                                     |
|---|
| Aluminum  |
| Shell Surface Treatment:                            |
| Cadmium and nickel                                  |
| Included Contact Quantity:                          |
| 66 single mating end single contact grouping        |
| Included Contact Type:                              |
| Round pin single mating end single contact grouping |
| Thread Series Designator:                           |
| Unef  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:                                    |
|   |
| Demilitarization:                                   |
| No  |
| Fiia:   |

A039b0