Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-312-2416

# Body Style:

Straight shape

# **Overall Length:**

Between 3.040 inches and 3.060 inches

### **Overall Height:**

0.605 inches

#### **Overall Width:**

Between 0.240 inches and 0.260 inches

#### Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

#### **Contact Removability:**

Nonremovable single mating end single contact grouping

### Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

#### **Polarization Method:**

Guide pin/socket

### **Connector Locking Method:**

Friction

# Features Provided:

Closed entry contact

#### **Terminal Location:**

Back single mating end single contact grouping

# **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

#### **Insert Material:**

Plastic polyphenylene single mating end and glass fiber single mating end

# **Contact Surface Treatment Specification:**

Mil-g-45204, type 2, cl 1, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2

federal specification 2nd treatment response single mating end single contact grouping

# **Terminal Type:**

Printed circuit single mating end single contact grouping

#### **Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping or qq-c-533 federal specification single material response single mating end single contact grouping or qq-b-750 federal specification single material response single mating end single contact grouping

#### **Guide Design And Location:**

D shape socket right-hand top at 12 oclock

#### **Included Contact Quantity:**

54 single mating end single contact grouping

# Included Contact Type:

Pound socket single mating and single contact grouping



Precious Material And Location: Contact surfaces gold

Precious Material And Weight:

0.054 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.