Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-312-2494

| Body Style: |
|--|
| |
| Straight type |
| Overall Length: 4.900 inches |
| 4.900 mones Overall Height: |
| 0.605 inches |
| Overall Width: |
| |
| Unthreaded Mounting Hole Diameter: |
| 0.120 inches |
| Distance Between Mounting Facility Centers: |
| 4.650 inches |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 122 single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Polarization Method: |
| Guide pin/socket |
| Connector Locking Method: |
| Friction |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping |
| Insert Material: |
| Plastic diallyl phthalate glass filled single mating end |
| Contact Surface Treatment Specification: |
| Mil-g-45204, type 2, cl 1 military specification single treatment response single mating end single contact grouping |
| Terminal Type: |
| Solder well single mating end single contact grouping |
| Contact Material Specification: |
| Qq-b-530 federal specification single material response single mating end single contact grouping |
| Guide Design And Location: |
| D shape socket right-hand at 12 oclock |
| Insert Material Specification: |
| Mil-m-14 military specification single material response single mating end |
| Included Contact Quantity: |
| |

122 single mating end single contact grouping



Included Contact Type: Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.122 gold grains, troy **Precious Material:** Gold Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.