

View Online at <https://aerobasegroup.com/nsn/5935-01-312-4629>

Body Style:

Right angle type

Overall Length:

Between 4.895 inches and 4.905 inches

Overall Width:

Between 0.540 inches and 0.560 inches

Body Height:

Between 0.395 inches and 0.405 inches

Environmental Protection:

Shock resistant and vibration resistant and corrosion resistant and humidity resistant and fungus resistant

Unthreaded Mounting Hole Diameter:

Between 0.115 inches and 0.125 inches

Distance Between Mounting Facility Centers:

Between 4.645 inches and 4.655 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

122 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Polarization Method:

Guide pin/socket

Connector Locking Method:

Friction

End Application:

1440-01-215-4868 armament subsystem, helicopter, guided missile launcher

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping or gold single mating end single contact grouping and copper single mating end single contact grouping

Insert Material:

Plastic polyphenylene single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 1, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2 federal specification 2nd treatment response single mating end single contact grouping or mil-g-45204, type 2, cl 1, grade c military specification 3rd treatment response single mating end single contact grouping and mil-c-14550, cl 4 military specification 4th treatment response single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping or qq-c-533 federal specification single material response single mating end single contact grouping or qq-b-750 federal specification single material response single mating end

Insert Material Specification:

Mil-m-24519 military specification single material response single mating end

Included Contact Quantity:

122 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.122 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.