Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-312-4631

Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Rectangular shape, angle
Overall Length:
2.175 inches
Overall Height:
0.524 inches
Overall Width:
1.186 inches
Environmental Protection:
Moisture resistant and salt water resistant and shock resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
0.125 inches
Distance Between Mounting Facility Centers:
Between 1.795 inches and 1.805 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
100 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
Mating end and jackscrew
Shell Type:
Solid
Connector Locking Method:
Post jacksocket
End Application:
1440-01-215-4868 armament subsystem
Thready Qty Per Inch (tpi):
40
Thread Size:
0.112 inches
Terminal Location:
Side single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping



Contact Surface Treatment: Gold single mating end single contact grouping **Insert Material:** Plastic epoxy single mating end or plastic polyphenylene single mating end and plastic epoxy single mating end **Contact Surface Treatment Specification:** Mil-g-45204, type 2, grade c, cl 1 military specification single treatment response single mating end single contact grouping **Terminal Type:** Pin single mating end single contact grouping Shell Material: Aluminum alloy 6061 or aluminum alloy 380.0 **Shell Surface Treatment:** Nickel **Shell Surface Treatment Specification:** Mil-c-26074 military specification single treatment response **Shell Material Specification:** Qq-a-250/11 federal specification 1st material response or qq-a-200/8 federal specification 1st material response or qq-a-591 federal specification 2nd material response Unable To Decode: Unable to decode and unable to decode **Included Contact Quantity:** 100 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Special Features:** Jackscrew type-female and location-right handandjackscrew type-female and location-left hand **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.100 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unc Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.