NSN 5935-01-312-6481

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-312-6481

Thread Class: 2a and 2b **Thread Direction:** Right-hand **Body Style:** Rectangular shape **Overall Length:** Between 2.275 inches and 2.285 inches Center To Center Distance Between Mounting Facilities Parallel To Length: Between 1.965 inches and 1.975 inches **Overall Width:** Between 1.125 inches and 1.135 inches **Environmental Protection:** Humidity resistant and shock resistant and thermal shock resistant and vibration resistant and fungus resistant **Unthreaded Mounting Hole Diameter:** 0.112 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:** Between 0.495 inches and 0.505 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 66 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Jackscrew **Connector Locking Method:** Jackscrew-socket **Operating Tempurature Rating:** Between -55.0 degrees celsius and 125.0 degrees celsius Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.138 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:**

Contact Surface Treatment:

Copper alloy single mating end single contact grouping

Gold single mating end single contact grouping and copper single mating end single contact grouping

NSN 5935-01-312-6481

Electrical Receptacle Connector - Page 2 of 2



Insert Material:
Plastic diallyl phthalate glass filled single mating end
Terminal Type:
Crimp single mating end single contact grouping
Insert Material Specification:
Mil-m-14, ty sdg-f military specification single material response single mating end
Unable To Decode:
Unable to decode and unable to decode
Included Contact Quantity:
66 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Special Features:
Jackscrew type-female and location-right handandjackscrew type-male and location-left hand
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.066 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-m-14 spec.