

View Online at <https://aerobasegroup.com/nsn/5935-01-312-6691>

Thread Direction:

Right-hand

Body Style:

Straight shape

Overall Length:

Between 175.3 millimeters and 175.7 millimeters

Overall Height:

17.8 millimeters

Overall Width:

7.05 millimeters

Environmental Protection:

Shock resistant and vibration resistant and corrosion resistant and humidity resistant and fungus resistant

Distance Between Mounting Facility Centers:

Between 167.3 millimeters and 167.9 millimeters

Threaded Device Type:

Mounting stud

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Connector Locking Method:

Friction

Operating Temperature Rating:

Between -65.0 degrees celsius and 125.0 degrees celsius

Thread Size:

2.5 millimeters

Thread Pitch In Millimeters:

0.45

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping or gold single mating end single contact grouping and copper single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate glass filled single mating end or plastic polyester glass filled single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 1, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2 federal specification 2nd treatment response single mating end single contact grouping or mil-g-45204, type 2, cl 1, grade c military specification 3rd treatment response single mating end single contact grouping and mil-c-14550, cl 4 military specification 4th treatment response single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping or qq-c-533 federal specification single material response single mating end single contact grouping or qq-c-750 federal specification single material response single mating end single contact grouping

Guide Design And Location:

Key shape socket left-hand at 3 oclock and key shape socket right-hand at 3 oclock

Insert Material Specification:

Mil-m-14, ty sdg-f or ty gdi-30f military specification 1st material response single mating end or mil-m-24519, ty gpt-30f or gst-40f military specification 2nd material response single mating end

Thread Tolerance Class:

6h external

Included Contact Quantity:

120 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.120 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-dod-c-55302 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Iso s

Specification Data:

81349-dod-c-55302/160 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-std-15001