

View Online at <https://aerobasegroup.com/nsn/5935-01-313-0786>

Body Style:

Straight shape, pc type

Overall Length:

Between 3.646 inches and 3.676 inches

Overall Height:

0.687 inches

Overall Width:

Between 0.325 inches and 0.345 inches

Environmental Protection:

Humidity resistant and salt water resistant and shock resistant and thermal shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

0.110 inches and 0.140 inches

Distance Between Mounting Facility Centers:

Between 3.399 inches and 3.413 inches

Board Accommodated Length:

2.966 inches single board and 2.978 inches single board

Board Accommodated Width:

Between 0.054 inches and 0.071 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

Bridged contacts inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

550.0 single mating end single contact grouping

Polarization Method:

Fixed contact to contact

Connector Locking Method:

Spring friction

End Application:

Receiving set, sonar an/bqr-15

Operating Temperature Rating:

Between -65.0 degrees celsius and 125.0 degrees celsius

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping or gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate glass filled single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type ii, class 1 military specification 1st treatment response single mating end single contact grouping and mil-g-45204, type i, grade a military specification 1st treatment response single mating end single contact grouping and mil-c-14550, class 4 military specification 2nd treatment response single mating end single contact grouping or mil-g-45204, type ii, class 1 military specification 3rd treatment response single mating end single contact grouping and mil-g-45204, type i, grade a military specification 3rd treatment response single mating end single contact grouping and qq-n-290, class 2 federal specification 4th treatment response single mating end single contact grouping

Unable To Decode:

Unable to decode and unable to decode

Terminal Type:

Solder well single mating end single contact grouping

Contact Material Specification:

Astm-b-103, alloy c assn standard single material response single mating end single contact grouping

Insert Material Specification:

Mil-p-19833, type gdi-30f military specification single material response single mating end

Included Contact Quantity:

18 single mating end single contact grouping

Included Contact Type:

Bifurcated spring single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.018 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.