

View Online at <https://aerobasegroup.com/nsn/5935-01-313-0952>

Body Material:

Plastic

Thread Class:

2a and 2a and 2a

Thread Direction:

Right-hand and right-hand and right-hand

Mounting Hole Diameter:

Between 0.107 inches and 0.117 inches

Body Mounting Hole Accommodation Length:

Between 1.595 inches and 1.605 inches

Body Mounting Hole Accommodation Width:

Between 1.105 inches and 1.115 inches

Mounting Hole Style:

Rectangular, w/four mounting holes/slots

Contact Maximum Current Rating In Amps:

10.0

Contact Material:

Copper alloy

Contact Surface Treatment:

Gold and nickel

Accommodated Contact Quantity:

20

Center To Center Distance Between Outside Mounting Holes Along Length:

Between 0.995 inches and 1.005 inches

Center To Center Distance Between Outside Mounting Holes Along Width:

Between 1.432 inches and 1.442 inches

Mounting Method:

Threaded stud

Mounting Type For Which Designed:

Chassis

Thready Qty Per Inch (tpi):

40 and 32 and 40

Thread Size:

0.112 inches and 0.190 inches and 0.112 inches

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.020 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-12883 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc and unf and unc

Terminal Type And Quantity:

20 crimp

Specification Data:

81349-mil-c-12883/48 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A02300