Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-313-1388

Body Style:

Straight shape, external coupling

Overall Length:

1.367 inches

Overall Height:

1.688 inches

Overall Width:

1.688 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 1.156 inches and 1.297 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.156 inches and 1.297 inches

Distance From Mounting Shoulder To Front Face:

0.556 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

20-90 single mating end

Contact Maximum Current Rating In Amps:

41.0 single mating end 2nd contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end all contact groupings

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end all contact groupings

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

18.0

Shell Type:

Solid

Terminal Type:

Crimp single mating end all contact groupings

Included Contact Quantity:

3 single mating end 1st contact grouping

Included Contact Type:

Round socket single mating end all contact groupings

Test Data Document:

81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a



Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-26482 spec.