## NSN 5935-01-313-1390

Mil-std (military Standard):

Mil-c-26482 spec.

Electrical Receptacle Connector - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5935-01-313-1390

| Body Style:  |
|--|
| Straight shape, external coupling  |
| Overall Length:  |
| 1.367 inches   |
| Center To Center Distance Between Mounting Facilities Parallel To Height:  |
| Between 1.230 inches and 1.375 inches  |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:  |
| Between 1.230 inches and 1.375 inches  |
| Distance From Mounting Shoulder To Front Face:   |
| 0.556 inches   |
| Mating End Quantity:   |
| 1  |
| Contact Position Arrangement Style:  |
| 22-95 single mating end  |
| Contact Maximum Current Rating In Amps:  |
| 41.0 single mating end 1st contact grouping  |
| Contact Maximum Ac Voltage Rating In Volts:  |
| 500.0 single mating end all contact groupings  |
| Contact Maximum Dc Voltage Rating In Volts:  |
| 700.0 single mating end all contact groupings  |
| Shell Type:  |
| Solid  |
| Terminal Type:   |
| Crimp single mating end all contact groupings  |
| Included Contact Quantity:   |
| 6 single mating end 1st contact grouping   |
| Included Contact Type:   |
| Round pin single mating end all contact groupings  |
| Test Data Document:  |
| 81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain          |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                            |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| <del></del>  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A039b0   |