

View Online at <https://aerobasegroup.com/nsn/5935-01-313-2318>

Thread Class:

2a and 2a

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.169 inches

Overall Diameter:

0.803 inches

Environmental Protection:

Vibration resistant and shock resistant and thermal shock resistant and moisture resistant

Distance From Mounting Shoulder To Front Face:

Between 0.796 inches and 0.801 inches

Mounting Facility Thickness:

Between 0.045 inches and 0.160 inches

Threaded Device Type:

Coupling facility and mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

Tnc single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Contact Maximum Frequency Rating:

15.0 gigahertz single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Connector Cable Strain Relief Method:

Crimp type

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

End Application:

5840-01-141-4378 radar set

Operating Temperature Rating:

Between -65.0 degrees celsius and 105.0 degrees celsius

Thready Qty Per Inch (tpi):

28 and 28

Thread Size:

0.438 inches and 0.500 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic polytetrafluoroethylene single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Contact Material Specification:

Qq-c-530, 1/2 hard federal specification single material response single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Nickel

Shell Surface Treatment Specification:

Qq-n-290 federal specification single treatment response

Shell Material Specification:

Qq-b-626, 1/2 hard federal specification single material response

Insert Material Specification:

Mil-p-19468 military specification single material response single mating end

Included Contact Quantity:

1 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round w/flat

Included Contact Type:

Coaxial socket single mating end single contact grouping

Special Features:

Furnished items - gasket

Precious Material And Location:

Contact surface gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unef and unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.