Electrical Plug Connector - Page 1 of 3

View Online at https://aerobasegroup.com/nsn/5935-01-313-3904



Thread Class: 2b Thread Direction:

Right-hand

Body Style:

Angle shape w/cable clamp

Overall Diameter:

2.718 inches

Body Angle In Deg:

90.0

Cable Entrance Diameter:

Between 1.180 inches and 1.611 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

40-53 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

13.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

80.0

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling ring

Connector Cable Strain Relief Method:

Cable clamp

End Application:

Receiving set, sonar an/bqr-15

Distance From Centerline To Connector End:

2.994 inches

Distance From Centerline To Cable End:

2.270 inches

Thready Qty Per Inch (tpi):

16

Thread Size:

2.500 inches

NSN 5935-01-313-3904

Electrical Plug Connector - Page 2 of 3



Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping

Insert Material:

Rubber chloroprene class cr single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 1, grade a military specification 1st treatment response single mating end single contact grouping and mil-g-45204, type ii,

grade c, class 1 military specification 1st treatment response single mating end single contact grouping and

Terminal Type:

Crimp single mating end single contact grouping

Contact Material Specification:

Qq-b-626, composition 260 or composition ii federal specification single material response single mating end single contact grouping

Shell Material:

Aluminum alloy 380.0

Shell Surface Treatment:

Cadmium and chromate

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification all treatment responses

Shell Material Specification:

Qq-a-591 federal specification single material response

Insert Material Specification:

Mil-std-417, grade sc715 military standard single material response single mating end

Included Contact Quantity:

60 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.060 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Un

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

NSN 5935-01-313-3904

Electrical Plug Connector - Page 3 of 3



Mil-std (military Standard):

Mil-g-45204 spec.