

View Online at <https://aerobasegroup.com/nsn/5935-01-313-5144>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

0.978 inches

Overall Diameter:

Between 1.359 inches and 1.391 inches

Distance From Mounting Shoulder To Front Face:

Between 0.691 inches and 0.722 inches

Mounting Facility Thickness:

Between 0.062 inches and 0.125 inches

Threaded Device Type:

Mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

14-5 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

22.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

900.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

1250.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

268.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

End Application:

Receiving set, sonar an/bqr-15

Thready Qty Per Inch (tpi):

20

Thread Size:

1.000 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Copper single mating end single contact grouping and gold single mating end single contact grouping

Insert Material:

Rubber single mating end

Contact Surface Treatment Specification:

Mil-c-14550, cl 4 military specification 1st treatment response single mating end single contact grouping and mil-g-45204, type 2, cl 2 military specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and chromate

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl c federal specification all treatment responses

Shell Material Specification:

Qq-a-591 federal specification single material response

Included Contact Quantity:

5 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.025 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-14550 spec.