Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-314-2333

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Straight shape, rectangular

Overall Length:

1.590 inches

Overall Height:

0.990 inches

Overall Width:

2.275 inches

Environmental Protection:

Thermal shock resistant and heat resistant and cold resistant

Unthreaded Mounting Hole Diameter:

0.156 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.550 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.900 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

52 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

13.0 single mating end single contact grouping

Polarization Method:

Polarization boss

Connector Locking Method:

Jackscrew

Operating Tempurature Rating:

Between -54.0 degrees celsius and 125.0 degrees celsius

Thready Qty Per Inch (tpi):

28

Thread Size:

0.250 inches

Terminal Location:

Back single mating end single contact grouping



Contact Material:	
Copper alloy single	e mating end single contact grouping
Contact Surface	Treatment:
Gold single mating	end single contact grouping and copper single mating end single contact grouping
Insert Material:	
Plastic diallyl phtha	alate single mating end
Contact Surface	Treatment Specification:
Mil-g-45204, type	2, grade c or d, cl 1 military specification 1st treatment response single mating end single contact grouping
Terminal Type:	
Crimp single matir	ng end single contact grouping
Contact Material	Specification:
Qq-b-626 federal s	specification single material response single mating end single contact grouping
Insert Material Sp	pecification:
Mil-m-14, sdg-f mi	litary specification single material response single mating end
Included Contact	Quantity:
52 single mating e	nd single contact grouping
Included Contact	Туре:
Round pin single r	nating end single contact grouping
Precious Materia	And Location:
Contact surfaces g	gold
Precious Materia	I And Weight:
0.052 gold grains,	troy
Precious Materia	
Gold	
Thread Series De	signator:
Unf	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A039b0	
Mil-std (military S	Standard):
Mil-g-45204 spec.	