# NSN 5935-01-314-2334

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-314-2334 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape, rectangular **Overall Length:** 1.170 inches **Overall Height:** 1.860 inches **Overall Width:** 2.875 inches **Environmental Protection:** Thermal shock resistant and heat resistant and cold resistant **Unthreaded Mounting Hole Diameter:** 0.156 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.760 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 2.500 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 158 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 13.0 single mating end single contact grouping **Polarization Method:** Polarization boss **Connector Locking Method:** Post jacksocket **Operating Tempurature Rating:** Between -54.0 degrees celsius and 125.0 degrees celsius Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches

**Terminal Location:** 

Back single mating end single contact grouping

# NSN 5935-01-314-2334

Electrical Receptacle Connector - Page 2 of 2



#### **Contact Material:**

Copper alloy single mating end single contact grouping

#### **Contact Surface Treatment:**

Gold single mating end single contact grouping and copper single mating end single contact grouping

#### **Insert Material:**

Plastic diallyl phthalate single mating end

# **Contact Surface Treatment Specification:**

Mil-g-45204, ty ii, grade c or d, cl 1 military specification 1st treatment response single mating end single contact grouping

### **Terminal Type:**

Crimp single mating end single contact grouping

#### **Contact Material Specification:**

Qq-b-626 federal specification single material response single mating end single contact grouping

#### **Insert Material Specification:**

Mil-m-14, ty sdg-f military specification single material response single mating end

#### **Included Contact Quantity:**

158 single mating end single contact grouping

#### **Included Contact Type:**

Round socket single mating end single contact grouping

### **Precious Material And Location:**

Contact surfaces gold

# **Precious Material And Weight:**

0.158 gold grains, troy

# **Precious Material:**

Gold

# **Thread Series Designator:**

Unf

#### Shelf Life:

N/a

# **Unit Of Measure:**

--

#### **Demilitarization:**

No

# Fiig:

A039b0

# Mil-std (military Standard):

Mil-g-45204 spec.