Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-314-2334

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Straight shape, rectangular

Overall Length:

1.170 inches

Overall Height:

1.860 inches

Overall Width:

2.875 inches

Environmental Protection:

Thermal shock resistant and heat resistant and cold resistant

Unthreaded Mounting Hole Diameter:

0.156 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.760 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

2.500 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

158 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

13.0 single mating end single contact grouping

Polarization Method:

Polarization boss

Connector Locking Method:

Post jacksocket

Operating Tempurature Rating:

Between -54.0 degrees celsius and 125.0 degrees celsius

Thready Qty Per Inch (tpi):

28

Thread Size:

0.250 inches

Terminal Location:

Back single mating end single contact grouping

NSN 5935-01-314-2334

Electrical Receptacle Connector - Page 2 of 2



| Contact Mater | |
|------------------|---|
| | ngle mating end single contact grouping |
| Contact Surfac | |
| | ting end single contact grouping and copper single mating end single contact grouping |
| Insert Material | |
| | hthalate single mating end |
| | ce Treatment Specification: |
| | ii, grade c or d, cl 1 military specification 1st treatment response single mating end single contact groupin |
| Terminal Type | |
| | ating end single contact grouping |
| | ial Specification: |
| | al specification single material response single mating end single contact grouping |
| Insert Material | Specification: |
| Mil-m-14, ty sdg | g-f military specification single material response single mating end |
| Included Cont | act Quantity: |
| 158 single mati | ng end single contact grouping |
| Included Cont | act Type: |
| Round socket s | single mating end single contact grouping |
| Precious Mate | rial And Location: |
| Contact surface | es gold |
| Precious Mate | rial And Weight: |
| 0.158 gold grain | ns, troy |
| Precious Mate | rial: |
| Gold | |
| Thread Series | Designator: |
| Unf | |
| Shelf Life: | |
| N/a | |
| Unit Of Measu | re: |
| | |
| Demilitarizatio | n: |
| No | |
| Fiig: | |
| A039b0 | |
| Mil-std (militar | y Standard): |
| Mil-g-45204 sp | ec. |