

View Online at <https://aerobasegroup.com/nsn/5935-01-314-6351>

Body Style:

Straight shape, pc type

Overall Length:

Between 4.425 inches and 4.445 inches

Overall Width:

0.350 inches

Unthreaded Mounting Hole Diameter:

0.125 inches

Distance Between Mounting Facility Centers:

4.175 inches

Board Accommodated Length:

3.700 inches single board

Board Accommodated Width:

0.200 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of independent contacts inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

600.0 single mating end single contact grouping

Connector Locking Method:

Friction

End Application:

6740-01-193-2018 printer-processor, p

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate glass filled single mating end

Terminal Type:

Wire wrap single mating end single contact grouping

Insert Material Specification:

Mil-m-14 ty sdg-f military specification single material response single mating end

Included Contact Quantity:

72 single mating end single contact grouping

Included Contact Type:

Bifurcated spring single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.072 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.