## NSN 5935-01-314-7253

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-314-7253

**Thread Class:** 2a and 2b **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, internal coupling w/backshell **Overall Length:** 2.281 inches **Overall Diameter:** 1.469 inches **Environmental Protection:** Heat resistant and cold resistant **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 20-22 single mating end **Contact Removability:** Removable single mating end all contact groupings **Contact Maximum Current Rating In Amps:** 73.0 single mating end 2nd contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end all contact groupings **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end all contact groupings **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: **Connector Locking Method:** Internally threaded coupling ring **End Application:** 4935-01-104-9827 shop equipment, guided missile system **Operating Tempurature Rating:** Between -55.0 degrees celsius and 200.0 degrees celsius Thready Qty Per Inch (tpi): 18 and 18 **Thread Size:** 1.188 inches and 1.188 inches

## NSN 5935-01-314-7253

Electrical Plug Connector - Page 2 of 2



## **Terminal Location:** Back single mating end all contact groupings **Contact Material:** Copper alloy single mating end all contact groupings **Contact Surface Treatment:** Silver single mating end 2nd contact grouping **Insert Material:** Plastic melamine single mating end **Terminal Type:** Crimp single mating end all contact groupings **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium and chromate **Shell Surface Treatment Specification:** Mil-std-171, finish no. 1.1.1.3 military standard 1st treatment response **Included Contact Quantity:** 3 single mating end 2nd contact grouping **Included Contact Type:** Round pin single mating end all contact groupings **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.003 gold grains, troy and 0.015 silver grains, troy **Precious Material:** Gold and silver **Thread Series Designator:** Unef and unef Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig: A039b0 Mil-std (military Standard):

Mil-std-171 spec.