## NSN 5935-01-314-7260

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-314-7260 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 25.0 millimeters **Overall Diameter:** 24.0 millimeters **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 7-oct single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 75.0 and 125.0 and 160.0 and 285.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin **End Application:** 5865-01-236-4235 mobile electronic warfare support system Thread Length: 0.290 inches **Operating Tempurature Rating:** Between -65.0 degrees celsius and 125.0 degrees celsius Thready Qty Per Inch (tpi): **Thread Size: Terminal Location:** Back single mating end single contact grouping

24

0.625 inches

**Contact Material:** 

Copper single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

## **NSN 5935-01-314-7260**Electrical Plug Connector - Page 2 of 2



Insert Material:
Rubber chloroprene class cr single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum
Shell Surface Treatment:
Cadmium and chromate
Included Contact Quantity:
7 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.007 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0