

View Online at <https://aerobasegroup.com/nsn/5935-01-315-4392>

Thread Class:

2a and 2b

Thread Direction:

Right-hand

Body Style:

Straight shape, rectangular

Overall Length:

2.890 inches

Overall Height:

0.812 inches

Overall Width:

1.670 inches

Environmental Protection:

Humidity resistant and shock resistant and thermal shock resistant and vibration resistant

Distance Between Mounting Facility Centers:

Between 2.367 inches and 2.383 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

25-104 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

Polarization Method:

Jackscrew and shell

Shell Type:

Solid

Connector Locking Method:

Jackscrew-socket

Thread Length:

0.320 inches

Operating Temperature Rating:

Between -55.0 degrees celsius and 125.0 degrees celsius

Thread Qty Per Inch (tpi):

32

Thread Size:

0.164 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate glass filled single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, grade c, class 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, class 2 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping or qq-c-533 federal specification single material response single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and chromate

Shell Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification all treatment responses

Insert Material Specification:

Mil-m-14, type sdg-f military specification single material response single mating end or mil-p-19833, type gdi-30f military specification single material response single mating end

Shell Guide Type And Location Designator:

C pin

Unable To Decode:

Unable to decode and unable to decode

Included Contact Quantity:

104 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Special Features:

Jackscrew type-male and location-right hand and jackscrew type-female and location-left hand

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.104 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-28748 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.