## NSN 5935-01-316-0954

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-316-0954

**Body Style:** 

Straight shape

**Overall Length:** 

Between 2.415 inches and 2.435 inches

**Overall Height:** 

Between 0.310 inches and 0.330 inches

**Overall Width:** 

Between 0.475 inches and 0.495 inches

**Environmental Protection:** 

Heat resistant and cold resistant

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

2 rows of contacts non-inserted board single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

3.0 single mating end single contact grouping

**Connector Locking Method:** 

Friction

**Operating Tempurature Rating:** 

Between -55.0 degrees celsius and 125.0 degrees celsius

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy 172 single mating end single contact grouping

**Contact Surface Treatment:** 

Copper single mating end single contact grouping and gold single mating end single contact grouping

**Insert Material:** 

Plastic polyphenylene single mating end and glass fiber single mating end

**Contact Surface Treatment Specification:** 

Mil-c-14550 military specification 1st treatment response single mating end single contact grouping and mil-g-45204, ty ii, cl 1 military specification 2nd treatment response single mating end single contact grouping

**Terminal Type:** 

Printed circuit single mating end single contact grouping

**Contact Material Specification:** 

Qq-c-533 federal specification single material response single mating end single contact grouping

**Insert Material Specification:** 

Mil-m-24519, type gst-40f military specification all material responses single mating end

**Included Contact Quantity:** 

96 single mating end single contact grouping

**Included Contact Type:** 

Spring pincers single mating end single contact grouping

## NSN 5935-01-316-0954

Electrical Receptacle Connector - Page 2 of 2



Special Features:
Flexible flat ribbon cable bonded to underside
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.096 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A039b0

Mil-std (military Standard):

Mil-c-14550 spec.