NSN 5935-01-316-0962

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-316-0962 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape w/cable clamp **Overall Length:** 1.720 inches **Bushing Diameter:** 0.685 inches **Overall Height:** 1.125 inches **Overall Width:** 1.125 inches **Environmental Protection:** Thermal shock resistant and vibration resistant and shock resistant and corrosion resistant and moisture resistant **Unthreaded Mounting Hole Diameter:** 0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.844 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.844 inches **Cable Entrance Diameter:** 0.531 inches **Distance From Mounting Shoulder To Front Face:** 0.750 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** Nonstd single mating end **Contact Removability:** Removable single mating end single contact grouping **Shell Type:** Solid **Connector Locking Method:** Externally threaded shell

Compression nut

Operating Tempurature Rating:

Connector Cable Strain Relief Method:

Between -65.0 degrees celsius and 165.0 degrees celsius

NSN 5935-01-316-0962

Electrical Receptacle Connector - Page 2 of 2



Thready Qty Per Inch (tpi):
24
Thread Size:
0.625 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic polytetrafluoroethylene single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Copper alloy
Shell Surface Treatment:
Nickel
Shell Material Specification:
Qq-b-626 federal specification single material response
Insert Material Specification:
L-p-403 federal specification single material response single mating end
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Coaxial pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.005 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039h0