

View Online at <https://aerobasegroup.com/nsn/5935-01-316-5893>

Body Style:

Straight shape

Overall Length:

0.785 inches

Overall Height:

0.616 inches

Overall Width:

0.308 inches

Environmental Protection:

Moisture resistant and salt water resistant and shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

Between 0.088 inches and 0.091 inches

Distance Between Mounting Facility Centers:

Between 0.560 inches and 0.570 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

9 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Polarization Method:

Mating end

Shell Type:

Solid

Connector Locking Method:

Friction

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, grade c, cl 1 military specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy or steel

Shell Surface Treatment:

Cadmium or zinc

Shell Material Specification:

Qq-a-591 federal specification 1st material response or qq-s-766 federal specification 2nd material response

Insert Material Specification:

Mil-m-14, ty sdg-f or gdi-30f military specification single material response single mating end

Included Contact Quantity:

9 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.009 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.