NSN 5935-01-316-6699

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-316-6699

Body Style:

Angle shape, pcb type

Environmental Protection:

Heat resistant and cold resistant

Unthreaded Mounting Hole Diameter:

0.098 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

3 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end 1st contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end 1st contact grouping

Polarization Method:

Mating end

Connector Locking Method:

Friction

End Application:

Training set, countermeasures signals

Operating Tempurature Rating:

Between -55.0 degrees celsius and 105.0 degrees celsius

Terminal Location:

Side single mating end 1st contact grouping

Contact Material:

Copper alloy single mating end 1st contact grouping

Contact Surface Treatment:

Gold and nickel single mating end 1st contact grouping

Insert Material:

Plastic single mating end

Terminal Type:

Printed circuit single mating end 1st contact grouping

Included Contact Quantity:

42 single mating end 1st contact grouping

Included Contact Type:

Square pin single mating end 1st contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.042 gold grains, troy

Precious Material:

Gold

NSN 5935-01-316-6699

Electrical Receptacle Connector - Page 2 of 2



_				-		
C	h	0	Iŧ.		ife:	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0