

View Online at <https://aerobasegroup.com/nsn/5935-01-316-7346>

Body Style:

Straight shape

Overall Length:

1.026 inches

Overall Diameter:

0.560 inches

Distance From Mounting Shoulder To Front Face:

0.767 inches

Mounting Facility Thickness:

0.250 inches

Threaded Device Type:

Back shell and coupling facility and mounting bushing

Mating End Quantity:

2

Contact Position Arrangement Style:

Nonstd all mating ends

Contact Removability:

Nonremovable all mating ends single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

10000.0 all mating ends single contact grouping

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Contact Material:

Copper alloy all mating ends single contact grouping

Contact Surface Treatment:

Gold all mating ends single contact grouping

Insert Material:

Plastic polychlorotrifluoroethylene all mating ends

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response all mating ends single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Gold

Shell Surface Treatment Specification:

Mil-g-45204 military specification single treatment response

Included Contact Quantity:

1 all mating ends single contact grouping

Bushing Accommodation Hole Shape:

Round

Included Contact Type:

Coaxial socket all mating ends single contact grouping

Precious Material And Location:

Contact and body surfaces gold

Precious Material And Weight:

0.110 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.