Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-316-7359

View Online at https://aerobasegroup.com/nsn/5935-01-316-7359
Body Style:
Straight type
Overall Length:
3.350 inches
Overall Width:
0.550 inches
Body Height:
0.335 inches
Environmental Protection:
Heat resistant and cold resistant
Mating End Quantity:
1
Contact Position Arrangement Style:
3 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
1.0 single mating end single contact grouping
Connector Locking Method:
Friction
End Application:
Training set, countermeasures signals an/msr-t4
Operating Tempurature Rating:
Between -55.0 degrees celsius and 125.0 degrees celsius
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic polyester glass filled single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end single contact grouping
Terminal Type:
Pin single mating end single contact grouping
Included Contact Quantity:
Included Contact Quantity: 64 single mating end single contact grouping
64 single mating end single contact grouping

Contact surfaces gold



**Precious Material And Weight:** 

0.064 gold grains, troy

## **Precious Material:**

Gold

Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

Fiig:

A039b0

## Mil-std (military Standard):

Mil-g-45204 spec.