## NSN 5935-01-316-8028

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-316-8028

**Body Style:** Straight shape, insulation piercing **Overall Length:** 3.740 inches **Overall Height:** 0.457 inches **Overall Width:** 0.417 inches **Unthreaded Mounting Hole Diameter:** 0.110 inches **Distance Between Mounting Facility Centers:** 3.543 inches **Mating End Quantity: Contact Position Arrangement Style:** 3 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 1.0 single mating end single contact grouping **Polarization Method:** Mating end **Connector Locking Method:** Friction **End Application:** Training set, countermeasures signals an/msr-t4 **Operating Tempurature Rating:** Between -65.0 degrees celsius and 105.0 degrees celsius **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Insert Material:** Plastic single mating end **Terminal Type:** Insulation piercing single mating end single contact grouping **Included Contact Quantity:** 64 single mating end single contact grouping

**Included Contact Type:** 

Flat pin single mating end single contact grouping

## NSN 5935-01-316-8028

Electrical Receptacle Connector - Page 2 of 2



<b>Precious Material And Location:</b>
Contact surfaces gold
Precious Material And Weight:
0.064 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A039b0