NSN 5935-01-316-8028

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-316-8028

Body Style: Straight shape, insulation piercing **Overall Length:** 3.740 inches **Overall Height:** 0.457 inches **Overall Width:** 0.417 inches **Unthreaded Mounting Hole Diameter:** 0.110 inches **Distance Between Mounting Facility Centers:** 3.543 inches **Mating End Quantity: Contact Position Arrangement Style:** 3 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 1.0 single mating end single contact grouping **Polarization Method:** Mating end **Connector Locking Method:** Friction **End Application:** Training set, countermeasures signals an/msr-t4 **Operating Tempurature Rating:** Between -65.0 degrees celsius and 105.0 degrees celsius **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Insert Material:** Plastic single mating end **Terminal Type:** Insulation piercing single mating end single contact grouping **Included Contact Quantity:** 64 single mating end single contact grouping

Included Contact Type:

Flat pin single mating end single contact grouping

NSN 5935-01-316-8028

Electrical Receptacle Connector - Page 2 of 2



| Precious Material And Location: |
|--|
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.064 gold grains, troy |
| Precious Material: |
| Gold |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A039b0