## NSN 5935-01-316-8035

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-316-8035

**Body Style:** 

Right angle type

**Overall Length:** 

Between 6.140 inches and 6.160 inches

**Overall Height:** 

1.000 inches

**Overall Width:** 

0.440 inches

**Unthreaded Mounting Hole Diameter:** 

Between 0.141 inches and 0.142 inches

**Distance Between Mounting Facility Centers:** 

Between 5.840 inches and 5.860 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

2 rows of contacts non-inserted board single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

3.0 single mating end single contact grouping

Shell Type:

Solid

**Connector Locking Method:** 

Friction

**Operating Tempurature Rating:** 

Between -55.0 degrees celsius and 105.0 degrees celsius

**Terminal Location:** 

Side single mating end single contact grouping

**Contact Material:** 

Copper alloy 260 single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:** 

Plastic polyphenylene single mating end

**Contact Surface Treatment Specification:** 

Mil-g-45204, type 2, grade c, cl 1 military specification 1st treatment response single mating end single contact grouping

**Criticality Code Justification:** 

Feat

**Terminal Type:** 

Pin single mating end single contact grouping

**Contact Material Specification:** 

Qq-b-613 federal specification single material response single mating end single contact grouping

## NSN 5935-01-316-8035

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Aluminum alloy 6061
Shell Surface Treatment:
Chromate
Shell Surface Treatment Specification:
Mil-c-5541, cl 1a military specification single treatment response
Shell Material Specification:
Qq-a-200/8, temper t6510 federal specification single material response
Included Contact Quantity:
104 single mating end single contact grouping
Included Contact Type:
Flat pin single mating end single contact grouping
Special Features:
Pin number marking is 104 through 208
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.104 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.