Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-316-8039

| Thread Class: | |
|--|----|
| 2a and 2b and 2a | |
| Thread Direction: | |
| Right-hand and right-hand and right-hand | |
| Body Style: | |
| Rectangular shape | |
| Overall Length: | |
| 1.680 inches | |
| Center To Center Distance Between Mounting Facilities Parallel To Length: | |
| 1.375 inches | |
| Overall Height: | |
| 0.680 inches | |
| Overall Width: | |
| 0.750 inches | |
| Environmental Protection: | |
| Shock resistant and vibration resistant and humidity resistant and cold resistant and heat resista | nt |
| Unthreaded Mounting Hole Diameter: | |
| 0.093 inches | |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: | |
| 0.500 inches | |
| Threaded Device Type: | |
| Coupling facility and mounting stud | |
| Mating End Quantity: | |
| 1 | |
| Contact Position Arrangement Style: | |
| 104-20 single mating end | |
| Contact Removability: | |
| Nonremovable single mating end single contact grouping | |
| Contact Maximum Current Rating In Amps: | |
| 7.5 single mating end single contact grouping | |
| Polarization Method: | |
| Jackscrew | |
| Connector Locking Method: | |
| | |
| Features Provided: | |
| Closed entry contact | |
| Thready Qty Per Inch (tpi): | |
| 56 and 56 and 40 | |
| Thread Size: | |
| 0.086 inches and 0.086 inches and 0.112 inches | |
| Terminal Location: | |
| Back single mating end single contact grouping | |



| Contact Material: Copper alloy single mating end single contact grouping | |
|---|----------------|
| Contact Surface Treatment: | |
| Gold single mating end single contact grouping | |
| Insert Material: | |
| Plastic diallyl phthalate single mating end | |
| Terminal Type: | |
| Solder well single mating end single contact grouping | |
| Insert Material Specification: | |
| Mil-m-14, ty gdi-30 military specification single material response single mating | n end |
| Unable To Decode: | gona |
| Unable to decode and unable to decode | |
| Included Contact Quantity: | |
| 104 single mating end single contact grouping | |
| Included Contact Type: | |
| Round socket single mating end single contact grouping | |
| Special Features: | |
| Jackscrew type-male and location-right handandjackscrew type-male and loca | tion-left hand |
| Precious Material And Location: | |
| Contact surfaces gold | |
| Precious Material And Weight: | |
| 0.104 gold grains, troy | |
| Precious Material: | |
| Gold | |
| Thread Series Designator: | |
| Unc and unc | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A039b0 | |
| Mil-std (military Standard): | |
| Mil-m-14 spec. | |