NSN 5935-01-316-8040

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-316-8040 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape w/jackscrew **Overall Length:** Between 2.115 inches and 2.135 inches **Overall Height:** 1.470 inches **Overall Width:** Between 0.820 inches and 0.840 inches **Environmental Protection:** Heat resistant **Unthreaded Mounting Hole Diameter:** 0.149 inches **Distance Between Mounting Facility Centers:** Between 1.740 inches and 1.760 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 36 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 13.0 single mating end single contact grouping **Polarization Method:** Polarization boss **Connector Locking Method:** Jackscrew **Operating Tempurature Rating:** Between -54.0 degrees celsius and 125.0 degrees celsius Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.138 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

NSN 5935-01-316-8040

Electrical Receptacle Connector - Page 2 of 2



^	ant	+	Cir	faaa	Trea	4ma	nt.
u	ont	act	Sur	race	rrea	une	m:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, grade c or d class military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Contact Material Specification:

Qq-b-626 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-14, ty sdg-f military specification single material response single mating end

Included Contact Quantity:

36 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.036 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig: A039b0

Mil-std (military Standard):

Mil-g-45204 spec.