

View Online at <https://aerobasegroup.com/nsn/5935-01-317-0514>

Body Style:

Straight shape

Overall Length:

Between 0.660 inches and 0.680 inches

Overall Height:

Between 0.685 inches and 0.775 inches

Overall Width:

Between 0.065 inches and 0.075 inches

Environmental Protection:

Moisture resistant and salt water resistant and shock resistant and vibration resistant

Mating End Quantity:

1

Contact Position Arrangement Style:

1 row of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end 1st contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end 1st contact grouping

Polarization Method:

Contact

Connector Locking Method:

Friction

Operating Temperature Rating:

125.0 degrees celsius

Terminal Location:

Back single mating end 1st contact grouping

Contact Material:

Copper alloy single mating end 1st contact grouping

Contact Surface Treatment:

Gold single mating end 1st contact grouping

Insert Material:

Plastic polyester glass filled single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, grade c, class 1 military specification single treatment response single mating end 1st contact grouping

Criticality Code Justification:

Feat

Terminal Type:

Pin single mating end 1st contact grouping

Insert Material Specification:

Mil-p-46174, class 40, grade e military specification single material response single mating end or mil-p-24519, type gpt-30f military specification single material response single mating end

Included Contact Quantity:

12 single mating end 1st contact grouping

Included Contact Type:

Round socket single mating end 1st contact grouping

Special Features:

Contact position five filled for polarization

Precious Material And Location:

Contact and terminal surfaces gold

Precious Material And Weight:

0.012 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.