Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-317-0520

Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Right angle type
Overall Length:
1.185 inches
Overall Width:
0.606 inches
Body Height:
0.308 inches
Environmental Protection:
Thermal shock resistant and shock resistant and moisture resistant and corrosion resistant
Unthreaded Mounting Hole Diameter:
Between 0.091 inches and 0.101 inches
Distance Between Mounting Facility Centers:
Between 0.960 inches and 0.970 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Connector Locking Method:
Post jacksocket
Operating Tempurature Rating:
Between -55.0 degrees celsius and 125.0 degrees celsius
Thready Qty Per Inch (tpi):
56
Thread Size:
0.086 inches
Terminal Location:
Side single mating end single contact grouping

Electrical Receptacle Connector - Page 2 of 2



Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate glass filled single mating end or plastic polyester single mating end

Terminal Type:

Printed circuit single mating end single contact grouping

Shell Material:

Aluminum alloy 6061

Shell Surface Treatment:

Cadmium and chromate

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification all treatment responses

Shell Material Specification:

Qq-a-200/8, t6 federal specification single material response

Insert Material Specification:

Mil-m-14, ty sdg-f military specification 1st material response single mating end or mil-m-24519 military specification 2nd material response single mating end

Included Contact Quantity:

25 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.025 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.