## NSN 5935-01-317-1850

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-317-1850

**Body Style:** 

Straight shape

**Overall Length:** 

Between 0.960 inches and 0.980 inches

**Overall Height:** 

Between 0.685 inches and 0.775 inches

**Overall Width:** 

Between 0.065 inches and 0.075 inches

**Environmental Protection:** 

Moisture resistant and salt water resistant and shock resistant and vibration resistant

**Mating End Quantity:** 

4

**Contact Position Arrangement Style:** 

1 row of contacts non-inserted board single mating end

**Contact Removability:** 

Nonremovable single mating end 1st contact grouping

**Contact Maximum Current Rating In Amps:** 

3.0 single mating end 1st contact grouping

**Polarization Method:** 

Contact

**Connector Locking Method:** 

Friction

**Operating Tempurature Rating:** 

125.0 degrees celsius

**Terminal Location:** 

Back single mating end 1st contact grouping

**Contact Material:** 

Copper alloy single mating end 1st contact grouping

**Contact Surface Treatment:** 

Gold single mating end 1st contact grouping

**Insert Material:** 

Plastic polyester glass filled single mating end

**Contact Surface Treatment Specification:** 

Mil-g-45204, type 2, grade c, class 1 military specification single treatment response single mating end 1st contact grouping

**Criticality Code Justification:** 

Feat

**Terminal Type:** 

Pin single mating end 1st contact grouping

**Insert Material Specification:** 

Mil-p-46174, class 40, grade e military specification single material response single mating end or mil-p-24519, type gpt-30f military specification single material response single mating end

**Included Contact Quantity:** 

17 single mating end 1st contact grouping

## NSN 5935-01-317-1850

Electrical Receptacle Connector - Page 2 of 2



A039b0

Mil-std (military Standard):

Mil-g-45204 spec.