Electrical Plug Connector - Page 1 of 2





Thread Class: 2a **Thread Direction: Right-hand Body Style:** Hood, top opening w/clamp **Overall Length:** Between 3.555 inches and 3.565 inches **Overall Height:** 2.512 inches **Overall Width:** 0.562 inches **Environmental Protection:** Shock resistant and vibration resistant and corrosion resistant and humidity resistant and fungus resistant **Cable Entrance Diameter:** Between 0.500 inches and 0.860 inches **Threaded Device Type:** Coupling facility Mating End Quantity: **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Hood, top opening **Connector Locking Method:** Jackscrew-socket **Connector Cable Strain Relief Method:** Cable clamp **End Application:** Landing control central an/mpn-14k Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.138 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:**

1

Gold single mating end single contact grouping and copper single mating end single contact grouping

NSN 5935-01-317-3513 Electrical Plug Connector - Page 2 of 2



| Insert Material: | |
|---------------------------|---|
| Plastic diallyl phthalate | glass filled single mating end |
| Terminal Type: | |
| Solder well single mati | ng end single contact grouping |
| Shell Material: | |
| Aluminum alloy | |
| Shell Surface Treatme | ent: |
| Anodize | |
| Shell Surface Treatme | ent Specification: |
| Mil-a-8625 military spe | cification single treatment response |
| Shell Material Specifie | cation: |
| Qq-a-250 federal speci | fication single material response |
| Insert Material Specif | ication: |
| Mil-p-19833, ty gdi-30f | military specification all material responses single mating end or mil-m-14, ty sdg-f military specification all material |
| responses single matin | g end |
| Included Contact Qua | intity: |
| 23 single mating end si | ngle contact grouping |
| Included Contact Typ | e: |
| Round socket single m | ating end single contact grouping |
| Precious Material And | Location: |
| Contact surfaces gold | |
| Precious Material And | d Weight: |
| 0.023 gold grains, troy | |
| Precious Material: | |
| Gold | |
| Thread Series Design | ator: |
| Unc | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A039b0 | |
| Mil-std (military Stand | lard): |
| Mil-p-19833 spec. | |