# NSN 5935-01-317-4059

Thread Class: 2a and 2a and 2a Thread Direction:

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-317-4059

Right-hand and right-hand
Body Style:
Straight shape, external coupling
Overall Length:
1.312 inches
Overall Height:
1.000 inches
Overall Width:
1.155 inches
Environmental Protection:
Heat resistant and cold resistant and vibration resistant and shock resistant and moisture resistant
Threaded Device Type:
Back shell and coupling facility and mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
Nonstd single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Radio Frequency Type Contact Characteristic Impedance In Ohms:
50.0 single mating end single contact grouping
Operating Tempurature Rating:
Between -65.0 degrees celsius and 165.0 degrees celsius
Thready Qty Per Inch (tpi):
32 and 24 and 32
Thread Size:
0.750 inches and 0.625 inches and 0.750 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:

Insert Material:

**Contact Surface Treatment:** 

Plastic polytetrafluoroethylene single mating end

Gold single mating end single contact grouping

Copper alloy single mating end single contact grouping

## NSN 5935-01-317-4059

Electrical Receptacle Connector - Page 2 of 2



#### **Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping

#### **Terminal Type:**

Solder well single mating end single contact grouping

### **Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping or qq-c-533 federal specification single material response single mating end single contact grouping

**Shell Material:** 

Copper alloy

**Shell Surface Treatment:** 

Nickel

**Shell Material Specification:** 

Qq-b-626 federal specification single material response

**Insert Material Specification:** 

L-p-403 federal specification single material response single mating end

**Included Contact Quantity:** 

1 single mating end single contact grouping

**Bushing Accommodation Hole Shape:** 

Round w/flat

**Included Contact Type:** 

Coaxial socket single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.005 gold grains, troy

**Precious Material:** 

Gold

**Thread Series Designator:** 

Un and unef and un

**Specification Data:** 

01714-g645240 manufacturers specification control

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.